

Table of Contents

Importing Table from Text File (ASCII) 1

Command Line Arguments and 'Silent' Import 2

Importing Table from Text File (ASCII)

Use Project → Import Text Table menu item to import table(s) from text file(s), also referred to as ASCII file(s).

You may select multiple files in opened standard file dialog by holding Ctrl or Shift.

- If you open multiple files, you can select the file to preview in files drop-down list (in Text Input Preview frame)
- If you select incorrect file(s) by mistake, click on Open icon to open file dialog once again and select other file(s).
- You can set Create Figure or Create Fit Plot checkbox to create Figure of Fit Plot after importing:
 - If you select Figure, the created Figure will contain all imported data from all files
 - If you select Fit Plot, one Fit Plot will be created for each imported file
- You can enlarge a part of the preview plot by selecting an area by mouse (scale box zoom tool). Use context menu of the plot to change scale zoom to default.
- F5 key reloads the text file or reloads the data from clipboard.

Import Text Table(s)

Text Input Preview (first 256 lines, → = tab)

Results.txt

1X→Y
21.999999999999996→-0.08690813552
31.917999999999997→0.065942762132
41.835999999999994→0.418821700293
51.753999999999996→0.696159300951
61.671999999999997→0.879945912393
71.589999999999994→1.105575308704
81.507999999999996→1.364499758103
91.425999999999997→1.376226395779
101.343999999999999→1.486336934085
111.262→1.6389291444641938

File Format

Encoding: <System default>

Read all lines

Auto detect

☐ Exclude header lines: 3

☒ Get column names from line: 1

Separate names by: ☒ Delimiter ☐ Column width

Column delimiter or reg. expr.: Auto detect

Decimal separator: Auto detect (., or,)

In Project

Create: ☐ Figure ☒ Fit Plot(s) Line

X: AX Y: BY Y Err: <None>

Preview (you can rename columns here)

	AX	BY
1	2	-0.0869
2	1.918	0.0659
3	1.836	0.4188
4	1.754	0.6962
5	1.672	0.8799
6	1.59	1.1056
7	1.508	1.3645
8	1.426	1.3762
9	1.344	1.4863
10	1.262	1.6389
11	1.18	1.4699

Columns: 2; rows: 50

Import

Cancel

Command Line Arguments and 'Silent' Import

MagicPlot opens files which come as command line arguments on launch. MagicPlot Project files (.mppz) are detected as projects, all other files are treated as text files and Import dialog is opened. Text files will be imported in the current opened project.

'-silent' key in command line forces MagicPlot to import text files without opening import dialog. The previously used import setting are used in such case. If Fit Plot or Figure creation was selected in Import dialog last time new plots will be created.

Example for Windows OS: `MagicPlotPro.exe mydata.txt -silent`

Please make sure that your firewall software does not block MagicPlot loopback (127.0.0.1) request.

From:

<https://magicplot.com/wiki/> - **MagicPlot Manual**

Permanent link:

<https://magicplot.com/wiki/import?rev=1446974484>

Last update: **Tue Nov 1 18:53:05 2016**

